

Schlauchaufroller Baureihe ST

Typentabelle und Maßblatt

Type	Art.-Nr.	Aufrollbare Schlauchlänge in m in Abhängigkeit vom Schlauchaußen- Ø in mm				Nennweite / Gewinde		Max. Druck	Ge- wicht	Abmessungen in mm									Oberfläche
		15	20	25	30	mm	Zoll			bar	kg	A	B	C	D	E	F	G	
ST14/10	204001213101	14	12	7		10	3/8"	300	14	176	206	243	400	440	3/8"IG	78	48	476	pulverbeschichtet
ST14/10e	204001213102	14	12	7		10	3/8"	300	14	176	206	243	400	440	3/8"IG	78	48	476	Edelstahl
ST14/10ep	204001213103	14	12	7		10	3/8"	300	14	176	206	243	400	440	3/8"IG	78	48	476	elektropoliert
ST20/10	204001713101	20	17	10		10	3/8"	300	16	176	206	243	460	500	3/8"IG	78	48	536	pulverbeschichtet
ST20/10e	204001713102	20	17	10		10	3/8"	300	16	176	206	243	460	500	3/8"IG	78	48	536	Edelstahl
ST20/10ep	204001713103	20	17	10		10	3/8"	300	16	176	206	243	460	500	3/8"IG	78	48	536	elektropoliert
ST20/12	204001722101		17	10		12	1/2"	200	16	176	206	243	460	500	1/2"IG	78	48	536	Edelstahl
ST20/12e	204001722102		17	10		12	1/2"	200	16	176	206	243	460	500	1/2"IG	78	48	536	elektropoliert
ST20/19	204001732101		17	10	7	19	3/4"	200	17	176	206	258	460	500	3/4"IG	78	48	536	pulverbeschichtet
ST20/19e	204001732102		17	10	7	19	3/4"	200	17	176	206	258	460	500	3/4"IG	78	48	536	Edelstahl
ST20/19ep	204001732103		17	10	7	19	3/4"	200	17	176	206	258	460	500	3/4"IG	78	48	536	elektropoliert

* Änderungen und Irrtümer vorbehalten, alle Preise zzgl. Verpackung und Mwst.

Schlauchaufroller Baureihe ST

Type	Art.-Nr.	Aufrollbare Schlauchlänge in m in Abhängigkeit vom Schlauchaußen- Ø in mm			Nennweite / Gewinde		Max. Druck	Ge- wicht	Abmessungen in mm									Oberfläche	
ST40/10/2	204003713101	40	37		10	3/8"	300	25	282	312	349	460	500	3/8"IG	184	154	536	pulverbeschichtet	
ST40/10/2e	204003713102	40	37		10	3/8"	300	25	282	312	349	460	500	3/8"IG	184	154	536	Edelstahl	
ST40/10/2ep	204003713103	40	37		10	3/8"	300	25	282	312	349	460	500	3/8"IG	184	154	536	elektropoliert	
ST60/10/2e		57			10	3/8"	300	32,5	382	418	449	460	500	3/8"IG	284	254	536	Edelstahl	
ST40/12/1	204002022101	20	20	20	12	1/2"	200	19	282	312	349	460	500	1/2"IG	184	154	536	pulverbeschichtet	
ST40/12/1e	204002022102	20	20	20	12	1/2"	200	19	282	312	349	460	500	1/2"IG	184	154	536	Edelstahl	
ST40/12/2	204003722101	40	37	30	12	1/2"	200	25	282	312	349	460	500	1/2"IG	184	154	536	pulverbeschichtet	
ST40/12/2e	204003722102	40	37	30	12	1/2"	200	25	282	312	349	460	500	1/2"IG	184	154	536	Edelstahl	
ST40/19/1	204002032101		20	20	18	19	3/4"	200	20	282	312	364	460	500	3/4"IG	184	154	536	pulverbeschichtet
ST40/19/1e	204002032102		20	20	18	19	3/4"	200	20	282	312	364	460	500	3/4"IG	184	154	536	Edelstahl
ST40/19/1ep	204002032103		20	20	18	19	3/4"	200	20	282	312	364	460	500	3/4"IG	184	154	536	elektropoliert
ST40/19/2	204003632101		40	36	30	19	3/4"	200	26,5	382	412	464	460	500	3/4"IG	284	254	536	pulverbeschichtet
ST40/19/2e	204003632102		40	36	30	19	3/4"	200	26,5	382	412	468	460	500	3/4"IG	284	254	536	Edelstahl
ST40/19/2ep	204003632103		40	36	30	19	3/4"	200	26,5	382	412	468	460	500	3/4"IG	284	254	536	elektropoliert

Schlauchaufroller Baureihe ST

Maßskizze

